

PRO RGB3

Channel Letter LED Module

PRO RGB3 0.72W

- 160 degree angle lens that spreads light evenly for no hot spots
- Specially designed durable cover that withstands harsh environment and protects the LED
- High luminous efficacy guaranteed up to 160 lm/W (PRO3 HE)
- Easy installation with extra size cover of 3M tape and screw hole
- IP68 Waterproof and approved by UL, CE, RoHS
- Best LED solution for Channel Letter and Sign Box illumination
- Advanced performance with guaranteed even brightness
- Long life time 50,000 hours



DESCRIPTION

DURITE PRO is new premium model for LED professionals. PRO is powered by Tier 1 LED with the enhanced lens and wire for highest performance. The extra size cover of 3M tape makes easy installation and saving labor cost. Our ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

SPECIFICATIONS

Model	RGB3-FUYL72
Colors	RGB Full Color
Lumens	36 lm/W
Power	0.72 W
Input Voltage	12V DC
Forward Current	60 mA
Beam Angle	160°
Module Spacing	2 pcs/ft
Demension	2.76" x 0.67" x 0.4"
Weight	7.7g
Max in series	40 Mods
Operating Temp.	-4°F ~ 140°F / -20°C ~ 60°C
Life Time	50,000
IP Rating	IP68 Waterproof

COVERAGE CHART

Depth	3"	4"	5"	6"~8"
Max Stroke Single Row	8"	10"	12"	14"
Max Stroke Multi Rows	6"	10"	12"	14"
Mods per ft	2 pcs per ft			
Standard Run	50 pcs			
Max Run	50 pcs			

Parameters can be adjusted according to the desired brightness.

DIMENSION

