

# DURiTE MINI3

Channel Letter LED Module

## MINI3 0.48W

- Versatile wide angle lens with compact design
- Ensures excellent transmittance and uniform lighting
- 150 degree angle lens that spreads light evenly for no hot spots
- Specially designed durable cover that withstands harsh environment and protects the LED
- High luminous efficacy guaranteed up to 100 lm/W
- Easy installation with double sided 3M tape
- IP68 Waterproof and approved by UL, CE, RoHS
- Long life time 50,000 hours



## DESCRIPTION

DURiTE MINI3 Series is Specialized for Channel Letter Signs.

The LED is powered by Reliable LED that makes high performance and durability as Tier 1 LED.

Starux's most cost-efficient model and easy installation with double sided 3M tape.

The ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

## SPECIFICATIONS

Model	MINI3-30YG48	MINI3-65YG48	MINI3-10YG48
Colors	3000K	6500K	10000K
Lumens	100 lm/W	100 lm/W	94 lm/W
Power		0.48 W	
Input Voltage		12V DC	
CRI		80+ Ra	
Beam Angle		150°	
Module Spacing		4 pcs/ft	
Demension		1.18" x 0.35" x 0.32"	
Weight		2.5g	
Max in series		50 Mods	
Operating Temp.		-4°F ~ 140°F / -20°C ~ 60°C	
Life Time		50,000	
IP Rating		IP68 Waterproof	

## COVERAGE CHART

Depth	3"	4"	5"
Max Stroke Single Row	6"	8"	10"
Max Stroke Multi Rows	6"	8"	10"
Mods per ft	4 pcs per ft		
Standard Run	50 pcs		
Max Run	50 pcs		

Parameters can be adjusted according to the desired brightness.

## DIMENSION

