DURITE PRO3 HE



PRO3 HE 1,1W

- Ensures excellent transmittance and uniform lighting
- 160 degree angle lens that spreads light evenly for no hot spots
- Specially designed durable cover that withstands harsh environment and protects the LED
- High luminous efficacy guaranteed up to 160 lm/W
- Easy installation with extra size cover of 3M tape and screw hole
- IP68 Waterproof and approved by UL, CE, RoHS
- Best LED solution for Channel Letter and Sign Box illumination
- Advanced performance with guaranteed even brightenss
- Long life time 50,000 hours













DESCRIPTION

DURITE PRO is new premium model for LED professionals.

PR03-70EV11 HE

PRO is powered by Tier 1 LED with the enhanced lens and wire for highest performance.

The extra size cover of 3M tape makes easy installation and saving labor cost.

Our ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

PR03-10EV11 HE

SPECIFICATIONS

Model

Life Time


IP Rating

1-10400	1100 702 11112	TINOO TOEVITTIE	
Colors	7000K	10000K	
Lumens	160 lm/W	155 lm/W	
Power	1.1 W		
Input Voltage	12V DC		
CRI	70+ Ra		
Beam Angle	160°		
Module Spacing	2 pcs/ft		
Demension	2.76" x 0.67" x 0.4"		
Weight	7.7g		
Max in series	40 Mods		
Operating Temp.	-4°F ~ 140°F / -20°C ~ 60°C		

COVERAGE CHART

Depth	5"	6"	7"	8"~12"	
Max Stroke Single Row	8"	10"	12"	14"	
Max Stroke Multi Rows	6"	10"	12"	14"	
Mods per ft	2 pcs per ft				
Standard Run	40 pcs				
Max Run	40 pcs				
Parameters can be adjusted according to the desired brightness.					

DIMENSION



50,000

IP68 Waterproof