DURITE PR03



Channel Letter LED Module



PRO3 Regular 1.1W

- · Ensures excellent transmittance and uniform lighting
- 160 degree angle lens that spreads light evenly for no hot spots
- Specially designed durable cover that withstands harsh environment and protects the LED
- High luminous efficacy guaranteed up to 100 lm/W
- Easy installation with extra size cover of 3M tape and screw hole
- IP68 Waterproof and approved by UL, CE, RoHS
- Best LED solution for Channel Letter and Sign Box illumination
- Advanced performance with guaranteed even brightenss
- Long life time 50,000 hours



DESCRIPTION

DURITE PRO is new premium model for LED professionals.

PRO is powered by Tier 1 LED with the enhanced lens and wire for highest performance.

The extra size cover of 3M tape makes easy installation and saving labor cost.

Our ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

SPECIFICATIONS

COVERAGE CHART

Model	PR03-40HL11	PR03-50HL11	Depth	4"	5"	6"	7"~10"
Colors	4000K	5000K	Max Stroke Single Row	8"	10"	12"	14"
Lumens	100 lm/W		Max Stroke Multi Rows	6"	10"	12"	14"
Power	1.1 W		Mods per ft	2 pcs per ft			
Input Voltage	12V DC		Standard Run	50 pcs			
CRI	80+ Ra		Max Run	50 pcs			
Beam Angle	160°		Parameters can be adjusted according to the desired brightness.				
Module Spacing	2 pcs/ft						
Demension	2.76" × 0.67" × 0.4"		DIMENSION				
Weight	7.7g		DIMENSION				
Max in series	50 Mods			6.02" (153m	ım)		
Operating Temp.	-4°F ~ 140°F / -20°C ~ 60°C		0.4" (10.2mm) (10.2mm				
Life Time	50,000						
IP Rating	IP68 Waterproof						