DURITE PR03



PRO3 Saver 0.72W

- · Ensures excellent transmittance and uniform lighting
- 160 degree angle lens that spreads light evenly for no hot spots
- Specially designed durable cover that withstands harsh environment and protects the LED
- High luminous efficacy guaranteed up to 160 lm/W
- Easy installation with extra size cover of 3M tape and screw hole
- IP68 Waterproof and approved by UL, CE, RoHS
- Best LED solution for Channel Letter and Sign Box illumination
- Advanced performance with guaranteed even brightenss
- Long life time 50,000 hours



DESCRIPTION

DURITE PRO is new premium model for LED professionals.

PRO is powered by Tier 1 LED with the enhanced lens and wire for highest performance.

The extra size cover of 3M tape makes easy installation and saving labor cost.

Our ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

SPECIFICATIONS

COVERAGE CHART

Model	PR03-30HL72	PR03-65HL72	PR03-10HL72	Depth	3"	4"	5"	6"~8"
Colors	3000K	6500K	10000K	Max Stroke Single Row	8"	10"	12"	14"
Lumens		100 lm/W		Max Stroke Multi Rows	6"	10"	12"	14"
Power	0.72 W			Mods per ft	2 pcs per ft			
Input Voltage	12V DC			Standard Run	50 pcs			
CRI		80+ Ra	Max Run	50 pcs				
Beam Angle	160°			Parameters can be adjusted according to the desired brightness.				
Module Spacing		2 pcs/ft						
Demension		2.76" x 0.67" x 0.4"	DIMENSION					
Weight		7.7g						
Max in series		50 Mods	L	6.02" (153m	ım)			
Operating Temp.	-4°F	F ~ 140°F / -20°C ~ 6	0.4" (10.2mm) 2.76" (70mm) 3.27" (83mm) 2.76" (70mm)					
Life Time		50,000						
IP Rating		IP68 Waterproof						