DURITE ECO ECO3S Red 0.72W





FEATURES

- · Ensures excellent transmittance and uniform lighting
- 160 degree angle lens that spreads light evenly for no hot spots
- Specially designed durable cover that withstands harsh environment and protects the LED
- Easy installation with double sided 3M tape and screw holes
- IP68 Waterproof and approved by UL, CE, RoHS
- Non-Polarity technology makes better wiring
- Long life time 50,000 hours

DESCRIPTION

DURITE ECO Series is Specialized for Channel Letter Signs.

The LED is powered by Reliable Korean LED that makes high performance and durability as Tier 1 LED.


ECO has a built-in non-polarity function, so the installer works without worry about the wiring.

The ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

SPECIFICATIONS

Model	ECO3S 0.72W Single Color	Module Spacing	ng 2 pcs/ft	
Colors	Red	Demension	2.6" x 0.55" x 0.37"	
Wavelength(nm)	620~625(26 lm/W)	Weight	7.7g	
Power	0.72W	Max in series	50 Mods	
Input Voltage	12V DC	Operating Temp.	-4°F ~ 122°F / -20°C ~ 50°C	
Forward Current	60 mA	Life Time	50,000	
Beam Angle	160°	IP Rating	IP68 Waterproof	

DIMENSION



COVERAGE CHART

Depth	3"	4"	5"	6"~8"
Max Stroke Single Row	8"	10"	12"	14"
Max Stroke Multi Rows	6"	10"	12"	14"
Mods per ft	2 pcs per ft			

Parameters can be adjusted according to the desired brightness.