


DURiTE ECO

ECO RGB3S 0.72W

DURiTE ECO Series

Channel Letter LED Module



FEATURES

- Full color with natural color projection
- Ensures excellent transmittance and uniform lighting
- Specially designed durable cover that withstands harsh environment and protects the LED
- Easy installation with double sided 3M tape
- IP68 Waterproof and approved by UL, CE, RoHS
- Compact design with vivid and eliminates hot spots
- Lifespan 50,000 hrs

DESCRIPTION

DURiTE ECO Series is Specialized for Channel Letter Signs.

The LED is powered by Reliable Korean LED that makes high performance and durability as Tier 1 LED.


Starux's most cost-efficient model and easy installation with double sided 3M tape.

The ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

SPECIFICATIONS

Model	ECO RGB3S 0.72W			Module Spacing	2 mods/ft
Colors	RGB Full Color			Dimensions	2.8" x 0.6" x 0.4"
Wavelength(nm)	R:620~625	G:520~525	B:460~465	Weight	10g
Power	0.72W			Max in series	40 mods
Input Voltage	12V DC			Operating Temp.	-4°F ~ 122°F / -20°C ~ 50°C
Forward Current	60 mA			Lifespan	50,000 hrs
Beam Angle	130°			IP Rating	IP68 Waterproof

DIMENSIONS



COVERAGE CHART

Depth	3"	4"	5"	6"~8"
Max Stroke Single Row	8"	10"	12"	14"
Max Stroke Multi Rows	6"	10"	12"	14"
Modules per ft	2 mods per ft			

Parameters can be adjusted according to the desired brightness.