



# PRO3 Regular 1.1W

- · Ensures excellent transmittance and uniform lighting
- 160 degree angle lens that spreads light evenly for no hot spots
- Specially designed durable cover that withstands harsh environment and protects the LED
- High luminous efficacy guaranteed up to 100 lm/W
- Easy installation with extra size cover of 3M tape and screw hole
- IP68 Waterproof and approved by UL, CE, RoHS
- Best LED solution for Channel Letter and Sign Box illumination
- Advanced performance with guaranteed even brightenss
- Long life time 50,000 hours











## **DESCRIPTION**

DURITE PRO is new premium model for LED professionals.

PRO is powered by Tier 1 LED with the enhanced lens and wire for highest performance.

The extra size cover of 3M tape makes easy installation and saving labor cost.

Our ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

### **SPECIFICATIONS**


**IP Rating** 

Model	PR03-30HL11	PR03-65HL11	PR03-10HL11				
Colors	3000K	6500K	10000K				
Lumens	100 lm/W						
Power	1.1 W						
Input Voltage	12V DC						
CRI	80+ Ra						
Beam Angle	160°						
Module Spacing	2 pcs/ft						
Demension	2.76" x 0.67" x 0.4"						
Weight	7.7g						
Max in series	50 Mods						
Operating Temp.	-4°F	~ 140°F / -20°C ~ 6	0°C				
Life Time		50,000					

#### COVERAGE CHART

Depth	4"	5"	6"	7"~10"		
Max Stroke Single Row	8"	10"	12"	14"		
Max Stroke Multi Rows	6"	10"	12"	14"		
Mods per ft	2 pcs per ft					
Standard Run	50 pcs					
Max Run	50 pcs					
Parameters can be adjusted according to the desired brightness.						

#### DIMENSION



IP68 Waterproof